

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code MI590A-0
Product name Peroxide Reagent A (test vial)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Determination of Peroxides in Edible Oil.

1.3. Details of the supplier of the safety data sheet

Name Milwaukee Electronics Kft.
Full address Alsókikötő sor 11.
District and Country H6726 Szeged Hungary
Tel. +36-62-428-050
Fax +36-62-428-051

e-mail address of the competent person responsible for the Safety Data Sheet info@milwaukeeinst.com

1.4. Emergency telephone number

For urgent inquiries refer to
Austria tel.: +431 406 43 43 - Belgium tel.: 070/245.245 - Bulgaria tel.: +359 2 9154409 - Czech Republic tel.: +420 224 919 293, +420 224 915 402 - Denmark tel.: 8212 12 12 - Estonia tel.: 112 - Finland tel.: (09) 471 977 (direct) or (09) 4711 (exchange) - France tel. ORFILA (INRS) : + 33 (0)1 45 42 59 59 - Ireland tel.: 01 8092166 - Lithuania tel.: +370 5 236 20 52, +370 687 53378 - Malta tel: 2545 0000, Medicines & Poisons Info Office tel.: 2545 6504 - Norway tel.: 22 59 13 00 - Portugal tel.: 808 250 143 - Romania tel. 021.318.36.06 (8:00 – 15:00) – Slovakia tel.: +421 2 5477 4166 - Spain tel.: + 34 91 562 04 20 - Sweden tel.: 112; 08-331231 (9:00-17:00)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

| | | |
|--|-------|---|
| Flammable liquid, category 3 | H226 | Flammable liquid and vapour. |
| Substance or mixture corrosive to metals, category 1 | H290 | May be corrosive to metals. |
| Carcinogenicity, category 2 | H351 | Suspected of causing cancer. |
| Reproductive toxicity, category 2 | H361d | Suspected of damaging the unborn child. |
| Acute toxicity, category 3 | H331 | Toxic if inhaled. |
| Acute toxicity, category 4 | H302 | Harmful if swallowed. |
| Specific target organ toxicity - repeated exposure, category 1 | H372 | Causes damage to organs through prolonged or repeated exposure. |
| Skin corrosion, category 1A | H314 | Causes severe skin burns and eye damage. |
| Serious eye damage, category 1 | H318 | Causes serious eye damage. |

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



SECTION 2. Hazards identification ... / >>

Signal words: Danger

Hazard statements:

| | |
|-------|---|
| H226 | Flammable liquid and vapour. |
| H290 | May be corrosive to metals. |
| H351 | Suspected of causing cancer. |
| H361d | Suspected of damaging the unborn child. |
| H331 | Toxic if inhaled. |
| H302 | Harmful if swallowed. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H314 | Causes severe skin burns and eye damage. |

Precautionary statements:

| | |
|----------------|--|
| P201 | Obtain special instructions before use. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P280 | Wear protective gloves / protective clothing / eye protection / face protection. |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313 | IF exposed or concerned: Get medical advice / attention. |
| P391 | Collect spillage. |
| P404 | Store in a closed container. |

Contains: CHLOROFORM
ACETIC ACID

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

| Identification | x = Conc. % | Classification (EC) 1272/2008 (CLP) |
|--|---------------------|--|
| ACETIC ACID INDEX 607-002-00-6 | 50 \leq x < 80 | Flam. Liq. 3 H226, Met. Corr. 1 H290, Skin Corr. 1A H314, Eye Dam. 1 H318, Classification note according to Annex VI to the CLP Regulation: B |
| EC 200-580-7 | | Flam. Liq. 3 H226: \geq 80%, Met. Corr. 1 H290: \geq 10%, Skin Corr. 1A H314: \geq 90%, Skin Corr. 1B H314: \geq 25%, Skin Irrit. 2 H315: \geq 10%, Eye Dam. 1 H318: \geq 25%, Eye Irrit. 2 H319: \geq 10% |
| CAS 64-19-7 REACH Reg. 01-2119475328-30 CHLOROFORM INDEX 602-006-00-4 | 34,75 \leq x < 50 | Carc. 2 H351, Repr. 2 H361d, Acute Tox. 3 H331, Acute Tox. 4 H302, STOT RE 1 H372, Eye Irrit. 2 H319, Skin Irrit. 2 H315 |
| EC 200-663-8 CAS 67-66-3 REACH Reg. 01-2119486657-20 | | STOT RE 2 H373: \geq 5% LD50 Oral: 695 mg/kg, STA Inhalation vapours: 3 mg/l |

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

SECTION 4. First aid measures ... / >>

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

CHLOROFORM

Irritant effects, Cough, Shortness of breath, respiratory arrest, Dizziness, narcosis, agitation, spasms, inebriation, Nausea, Vomiting, Stomach/intestinal disorders, cardiovascular disorders, Headache, ataxia (impaired locomotor coordination). Drying-out effect resulting in rough and chapped skin.

ACETIC ACID

ACETIC ACID 100%: Irritation and corrosion, bronchitis, Shortness of breath, gastric spasms, Nausea, Vomiting, Circulatory collapse, shock, Risk of corneal clouding. Risk of blindness!.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

CHLOROFORM

Not combustible. Ambient fire may liberate hazardous vapours. Fire may cause evolution of: Hydrogen chloride gas, Phosgene.

ACETIC ACID

ACETIC ACID 100%: Combustible. Vapours are heavier than air and may spread along floors. Forms explosive mixtures with air at elevated temperatures. Development of hazardous combustion gases or vapours possible in the event of fire. Fire may cause evolution of: Acetic acid vapours.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

SECTION 6. Accidental release measures ... / >>

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition.

Storage class TRGS 510 (Germany): 3

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

| | | |
|-----|------------------|--|
| AUS | Österreich | Gesamte Rechtsvorschrift für Grenzwerteverordnung 2021 , Fassung vom 17.06.2021 |
| BEL | Belgique | Liste de valeurs limites d'exposition aux agents chimiques, livre VI du code du bien-être au travail |
| BGR | България | НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.) |
| CHE | Suisse / Schweiz | Valeurs limites d'exposition aux postes de travail: VME/VLE (SUVA). Grenzwerte am Arbeitsplatz: MAK (SUVA) |
| CYP | Κύπρος | Οι περὶ Αζθάλειας και Υγείας ζητην Διπαζία (Φημικοί Παπάγνηερ) (Τποποποιητικοί) Κανονιζμοί ηος 2019. Οι περὶ Ασφάλειας και Υγείας στην Εργασία (Καρκινογόνοι και Μεταλλαξιογόνοι Παράγοντες) (Τροποποιητικοί) Κανονισμοί του 2020 |
| CZE | Česká Republika | Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů |
| DEU | Deutschland | Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56 |
| DNK | Danmark | Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019 |
| ESP | España | Límites de exposición profesional para agentes químicos en España 2021 |
| EST | Eesti | Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööhutuse nõuded ning töokeskkonna keemiliste ohutegurite piinormid [RT I, 17.10.2019, 1 - jõust. 17.01.2020] |
| FRA | France | Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS |
| FIN | Suomi | HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 2020:25 |
| GRC | Ελλάδα | Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"» |

SECTION 8. Exposure controls/personal protection ... / >>

| | | |
|-----|----------------|--|
| HUN | Magyarország | Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről |
| HRV | Hrvatska | Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021) |
| IRL | Éire | 2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019) |
| LTU | Lietuva | Jsakymas dėl lietuvis higienos normos hn 23:2011 „cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai“ patvirtinimo |
| LVA | Latvija | Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības prasības saskarē ar ķīmiskajām vielām darba vietās" (prot. Nr. 32 18. §; prot. Nr. 1 22. §) |
| NOR | Norge | Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255 |
| POL | Polska | Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy |
| ROU | România | Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006 |
| SWE | Sverige | Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1) |
| SVK | Slovensko | NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov |
| SVN | Slovenija | Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19) |
| GBR | United Kingdom | EH40/2005 Workplace exposure limits (Fourth Edition 2020) |
| EU | OEL EU | Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC. |
| | TLV-ACGIH | ACGIH 2021 |

CHLOROFORM

| Threshold Limit Value | | | | | | | | |
|--|----------------------|----------|-----|--------------------|----------|------------------------|------------|---------|
| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations | | |
| | | mg/m3 | ppm | mg/m3 | ppm | | | |
| MAK | AUS | 10 | 2 | | | | | |
| VLEP | BEL | 10 | 2 | | | | | |
| MAK | CHE | 2,5 | 0,5 | 5 | 1 | | | |
| MAK | DEU | 2,5 | 0,5 | | | | | |
| TLV | DNK | 10 | 2 | 20 | 4 | | | |
| VLA | ESP | 10 | 2 | | | | | |
| VLEP | FRA | 10 | 2 | 250 | 50 | | | |
| HTP | FIN | 10 | 2 | 20 | 4 | | | |
| AK | HUN | 10 | | | | | | |
| OELV | IRL | 9,8 | 2 | | | | | |
| NDS/NDSch | POL | 8 | | | | | | |
| TLV | ROU | 10 | 2 | | | | | |
| NGV/KGV | SWE | 10 | 2 | | | | | |
| WEL | GBR | 9,9 | 2 | | | | | |
| OEL | EU | 10 | 2 | | | | | |
| TLV-ACGIH | | | 10 | | | | | |
| Predicted no-effect concentration - PNEC | | | | | | | | |
| Normal value in fresh water | | | | | | 0,146 | mg/l | |
| Normal value in marine water | | | | | | 0,015 | mg/l | |
| Normal value for fresh water sediment | | | | | | 0,45 | mg/kg/d | |
| Normal value for marine water sediment | | | | | | 0,09 | mg/kg/d | |
| Normal value for water, intermittent release | | | | | | 0,133 | mg/l | |
| Normal value of STP microorganisms | | | | | | 0,048 | mg/l | |
| Normal value for the terrestrial compartment | | | | | | 0,56 | mg/kg/d | |
| Health - Derived no-effect level - DNEL / DMEL | | | | | | | | |
| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
| | Acute | Acute | | Chronic | Chronic | Acute | Acute | Chronic |
| | local | systemic | | local | systemic | local | systemic | local |
| Inhalation | | | | VND | 0,18 | | | 2,5 |
| | | | | | mg/m3 | | | mg/m3 |
| Skin | | | | | | | 0,94 | VND |
| | | | | | | | mg/kg bw/d | |

SECTION 8. Exposure controls/personal protection ... / >>

ACETIC ACID

| Threshold Limit Value | | | | | | |
|-----------------------|---------|--------|-----|------------|-----|------------------------|
| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
| | | mg/m3 | ppm | mg/m3 | ppm | |
| MAK | AUS | 25 | 10 | 50 | 20 | |
| VLEP | BEL | 25 | 10 | 38 | 15 | |
| TLV | BGR | 25 | | 37 | | |
| MAK | CHE | 25 | 10 | 50 | 20 | |
| TLV | CYP | 25 | 10 | | | |
| TLV | CZE | 25 | | 35 | | |
| MAK | DEU | 25 | 10 | | | |
| TLV | DNK | 25 | 10 | 50 | 20 | |
| VLA | ESP | 25 | 10 | 37 | 15 | |
| TLV | EST | 25 | 10 | 25 | 10 | |
| VLEP | FRA | | | 25 | 10 | |
| HTP | FIN | 13 | 5 | 25 | 10 | |
| TLV | GRC | 25 | 10 | 37 | 15 | |
| AK | HUN | 25 | | 25 | | |
| GVI/KGVI | HRV | 25 | 10 | | | |
| OELV | IRL | 25 | 10 | 37 | 15 | |
| RD | LTU | 25 | 10 | | | |
| RV | LVA | 25 | 10 | | | |
| TLV | NOR | 25 | 10 | | | |
| NDS/NDSch | POL | 15 | | 30 | | |
| TLV | ROU | 25 | 10 | | | |
| NGV/KGV | SWE | 13 | 5 | 25 | 10 | |
| NPEL | SVK | 25 | 10 | | | |
| MV | SVN | 25 | 10 | | | |
| OEL | EU | 25 | 10 | 50 | 20 | |
| TLV-ACGIH | | | 10 | | 15 | |

Predicted no-effect concentration - PNEC

| | | |
|--|--------|-------|
| Normal value in fresh water | 3,058 | mg/l |
| Normal value in marine water | 0,3058 | mg/l |
| Normal value for fresh water sediment | 11,36 | mg/kg |
| Normal value for marine water sediment | 1,136 | mg/kg |
| Normal value for water, intermittent release | 30,58 | mg/l |
| Normal value of STP microorganisms | 85 | mg/l |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | | Effects on workers | | | |
|-------------------|----------------------|----------|---------|----------|--------------------|----------|---------|----------|
| | Acute | Acute | Chronic | Chronic | Acute | Acute | Chronic | Chronic |
| | local | systemic | local | systemic | local | systemic | local | systemic |
| Inhalation | 25 | VND | 25 | VND | 25 | VND | 25 | VND |
| | mg/m3 | | mg/m3 | | mg/m3 | | mg/m3 | |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

CHLOROFORM

Methods for measurement of the workplace atmosphere have to correspond to the requirements of norms UNI EN 482 and UNI EN 689.

ACETIC ACID

Methods for measurement of the workplace atmosphere have to correspond to the requirements of norms UNI EN 482 and UNI EN 689.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

SECTION 8. Exposure controls/personal protection ... / >>

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Properties | Value | Information |
|--|------------------|--|
| Appearance | liquid | |
| Colour | colourless | |
| Odour | pungent | |
| Melting point / freezing point | not available | |
| Initial boiling point | 60 °C | |
| Flammability | not available | |
| Lower explosive limit | not available | |
| Upper explosive limit | not available | |
| Flash point | 60 °C | Method:ASTM D92-18 |
| Auto-ignition temperature | not available | |
| Decomposition temperature | not available | |
| pH | < 1 | Method:ASTM D1293-18 Temperature: 25 °C |
| Kinematic viscosity | not available | |
| Solubility | soluble in water | |
| Partition coefficient: n-octanol/water | not available | |
| Vapour pressure | 61,26 mmHg | |
| Density and/or relative density | 1,26 | |
| Relative vapour density | not available | |
| Particle characteristics | not applicable | |

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

| | | | | |
|----------------------------|----------------|---|----------|---------|
| VOC (Directive 2010/75/EU) | 100,00 % | - | 1.257,09 | g/litre |
| VOC (volatile carbon) | 69,18 % | - | 869,71 | g/litre |
| Explosive properties | not applicable | | | |
| Oxidising properties | not applicable | | | |

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

ACETIC ACID

ACETIC ACID 100%: Vapour/air-mixtures are explosive at intense warming.

SECTION 10. Stability and reactivity ... / >>**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

CHLOROFORM

Heat-sensitive. Sensitivity to light. Stabilizer ethanol.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

CHLOROFORM

Risk of explosion with: Ammonia, Amines, nitrogen oxides, bases, Oxygen, alkali amides, organic nitro compounds, Alcohols, alkali hydroxides, strong alkalis, Fluorine, peroxi compounds, Alkaline earth metals, Alkali metals, Powdered metals, Methanol with alcoholates, Methanol with strong alkalis, Iron in powder form, various alloys sensitive to shock, Methanol with Sodium hydroxide, magnesium in powder form, Oxygen with alkali compounds, Aluminium in powder form, Acetone with alkali compounds, Potassium sensitive to shock, sodium sensitive to shock. Violent reactions possible with: phosphines, bis(dimethylamino)dimethyl tin, nonmetallic hydrogen compounds, Powdered metals, Light metals, Ketones, mineral acids, Strong oxidizing agents, semimetallic hydrogen compounds.

ACETIC ACID

ACETIC ACID 100%: Risk of explosion on contact with: chromium (IV) oxide, potassium permanganate, sodium peroxide, perchloric acid, phosphorus chloride, hydrogen peroxide. Can react dangerously with: alcohols, bromine pentafluoride, chlorosulphuric acid, dichromate-sulphuric acid, ethane diamine, ethylene glycol, potassium hydroxide, strong bases, sodium hydroxide, strong oxidising agent, nitric acid, ammonium nitrate, potassium tert-butoxide, oleum. Forms explosive mixtures with air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ACETIC ACID

ACETIC ACID 100%: Avoid exposure to sources of heat and naked flames.

10.5. Incompatible materials**CHLOROFORM**

Rubber, various plastics.

ACETIC ACID

ACETIC ACID 100%: Carbonates, hydroxides, many oxides and phosphates. Oxidising substances and bases.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**CHLOROFORM**

Acute oral toxicity, Symptoms: Nausea, Vomiting, Risk of aspiration upon vomiting, Aspiration may cause pulmonary oedema and pneumonitis. absorption - Acute inhalation toxicity, Acute toxicity estimate: 0.5 mg/l; aerosol, Symptoms: Cough, Shortness of breath, Possible damages: mucosal irritations, absorption - Acute dermal toxicity: Skin irritation, Rabbit, Result: slight irritation. Drying-out effect resulting in rough and chapped skin. Causes skin irritation. Eye irritation. Causes serious eye irritation - CMR effects, Carcinogenicity: Suspected of causing cancer - Teratogenicity: Suspected of damaging the unborn child - Specific target organ toxicity, repeated exposure, Target Organs: Liver, Kidney, Causes damage to organs through prolonged or repeated exposure.

ACETIC ACID

ACETIC ACID 100% - Acute oral toxicity, Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach., Nausea, Vomiting, Risk of aspiration upon vomiting., Pulmonary failure possible after aspiration of vomit - Acute inhalation toxicity, LCLO Rat: 39.95 mg/l, 4 h, Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages: damage of respiratory tract, Pneumonia, bronchitis, Inhalation may lead to the formation of oedemas in the respiratory tract., Symptoms may be delayed - Skin irritation, Rabbit, Result: Causes burns - Eye irritation, Rabbit, Result: Causes serious eye damage. Risk of blindness! Risk of corneal clouding. Germ cell mutagenicity, Genotoxicity in vitro, Ames test, Salmonella typhimurium, Result: negative - Mutagenicity (mammal cell test): chromosome aberration, Result: negative -

SECTION 11. Toxicological information ... / >>

Teratogenicity, Did not show teratogenic effects in animal experiments .

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

| | |
|--|---|
| ATE (Inhalation - vapours) of the mixture: | 6,00 mg/l |
| ATE (Oral) of the mixture: | 1390,00 mg/kg |
| ATE (Dermal) of the mixture: | Not classified (no significant component) |

CHLOROFORM

| | |
|----------------------------|---|
| LD50 (Dermal): | > 3980 mg/kg Rabbit |
| LD50 (Oral): | 695 mg/kg Rat |
| LC50 (Inhalation vapours): | 47,7 mg/l/4h Rat |
| STA (Inhalation vapours): | 3 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |

ACETIC ACID

| | |
|----------------------------|-------------------|
| LD50 (Dermal): | 1060 mg/kg Rabbit |
| LD50 (Oral): | 3310 mg/kg Rat |
| LC50 (Inhalation vapours): | 11,4 mg/l/4h Rat |

SKIN CORROSION / IRRITATION

Corrosive for the skin
Classification according to the experimental Ph value

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Suspected of causing cancer

REPRODUCTIVE TOXICITY

Suspected of damaging the unborn child

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Causes damage to organs

SECTION 11. Toxicological information ... / >>

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

CHLOROFORM

Toxicity to daphnia and other aquatic invertebrates, EC5 *E.sulcatum*: > 6,560 mg/l; 72 h (maximum permissible toxic concentration) - Toxicity to algae, IC5 *Scenedesmus quadricauda* (Green algae): 1,100 mg/l; 8 d (maximum permissible toxic concentration) - Toxicity to bacteria, EC5 *Pseudomonas putida*: 125 mg/l; 16 h (maximum permissible toxic concentration), EC50 activated sludge: 1,010 mg/l; 3 h .

ACETIC ACID

ACETIC ACID 100%: Toxicity to algae, IC5 *Scenedesmus quadricauda* (Green algae): 4,000 mg/l, 16 h, (maximum permissible toxic concentration) (Lit.) - Toxicity to bacteria, EC5 *Pseudomonas putida*: 2,850 mg/l, 16 h, neutral (maximum permissible toxic concentration) (Lit.), microtox test EC50 *Photobacterium phosphoreum*: 11 mg/l, 15 min .

CHLOROFORM

| | |
|----------------------|--|
| LC50 - for Fish | 18 mg/l/96h <i>Lepomis macrochirus</i> |
| EC50 - for Crustacea | 79 mg/l/48h <i>Daphnia magna</i> |

ACETIC ACID

| | |
|----------------------|---|
| LC50 - for Fish | > 300,8 mg/l/96h <i>Oncorhynchus mykiss</i> |
| EC50 - for Crustacea | > 300,82 mg/l/48h <i>Daphnia magna</i> |

12.2. Persistence and degradability

CHLOROFORM

Biodegradability 0 %; 14 d. Not readily biodegradable.

ACETIC ACID

ACETIC ACID 100%: Biodegradability 99 %, 30 d, Readily biodegradable - 95 %; 5 d, Readily eliminated from water - Biochemical Oxygen Demand (BOD) 880 mg/g (5 d) - Ratio BOD/ThBOD BOD5 76 %.

CHLOROFORM

| | |
|---------------------|--------|
| Solubility in water | 8 mg/l |
|---------------------|--------|

ACETIC ACID

| | |
|---------------------|--------------|
| Solubility in water | > 10000 mg/l |
| Rapidly degradable | |

12.3. Bioaccumulative potential

CHLOROFORM

Partition coefficient: n-octanol/water, log Pow: 2 (25 °C), (experimental). Bioaccumulation is not expected.

CHLOROFORM

| | |
|--|-----------|
| Partition coefficient: n-octanol/water | 2 Log Kow |
|--|-----------|

ACETIC ACID

| | |
|--|-------|
| Partition coefficient: n-octanol/water | -0,17 |
|--|-------|

12.4. Mobility in soil

CHLOROFORM

Distribution among environmental compartments, Adsorption/Soil log Koc: 1.72, (experimental). Mobile in soils.

SECTION 12. Ecological information ... / >>

ACETIC ACID

Partition coefficient: soil/water 1,153

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

CHLOROFORM

Henry constant 14084 Pa·m³/mol, Method: (experimental), Distribution preferentially in air. Discharge into the environment must be avoided.

ACETIC ACID

ACETIC ACID 100%: Biological effects, Harmful effect due to pH shift. Caustic even in diluted form. Discharge into the environment must be avoided.

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 2920

14.2. UN proper shipping name

ADR / RID: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Acetic Acid, Chloroform)

IMDG: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Acetic Acid, Chloroform)

IATA: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Acetic Acid, Chloroform)

14.3. Transport hazard class(es)

ADR / RID: Class: 8 Label: 8 (3)



IMDG: Class: 8 Label: 8 (3)



IATA: Class: 8 Label: 8 (3)



14.4. Packing group

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

SECTION 14. Transport information ... / >>

14.6. Special precautions for user

| | | | |
|------------|------------------------|-------------------------|--------------------------------|
| ADR / RID: | HIN - Kemler: 83 | Limited Quantities: 1 L | Tunnel restriction code: (D/E) |
| IMDG: | Special provision: 274 | Limited Quantities: 1 L | |
| IATA: | EMS: F-E, S-C | Maximum quantity: 30 L | Packaging instructions: 855 |
| | Cargo: | Maximum quantity: 1 L | Packaging instructions: 851 |
| | Pass.: | - | |
| | Special provision: | - | |

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c-H2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

| | | |
|---------------------|--------|--|
| Product | | |
| Point | 3 - 40 | |
| Contained substance | | |
| Point | 75 | |
| Point | 32 | CHLOROFORM REACH Reg.: 01-2119486657-20 |

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

CHLOROFORM

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 3: Severe hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

| | |
|---------------|--|
| Flam. Liq. 3 | Flammable liquid, category 3 |
| Met. Corr. 1 | Substance or mixture corrosive to metals, category 1 |
| Carc. 2 | Carcinogenicity, category 2 |
| Repr. 2 | Reproductive toxicity, category 2 |
| Acute Tox. 3 | Acute toxicity, category 3 |
| Acute Tox. 4 | Acute toxicity, category 4 |
| STOT RE 1 | Specific target organ toxicity - repeated exposure, category 1 |
| Skin Corr. 1A | Skin corrosion, category 1A |
| Eye Dam. 1 | Serious eye damage, category 1 |

SECTION 16. Other information ... / >>

| | |
|---------------|---|
| Eye Irrit. 2 | Eye irritation, category 2 |
| Skin Irrit. 2 | Skin irritation, category 2 |
| H226 | Flammable liquid and vapour. |
| H290 | May be corrosive to metals. |
| H351 | Suspected of causing cancer. |
| H361d | Suspected of damaging the unborn child. |
| H331 | Toxic if inhaled. |
| H302 | Harmful if swallowed. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H314 | Causes severe skin burns and eye damage. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

SECTION 16. Other information ... / >>

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

03 / 08 / 09 / 11 / 12.